

# XG17-25kW

## Three Phase On-Grid Solar Inverter



 Efficient  
Higher Revenue

- 2 MPP Trackers, high single circuit tracking accuracy, fast dynamic response
- 160% DC Input Oversizing
- Maximum efficiency 98.4%. Wide MPPT voltage range: 200V-1000V
- Compatible with high power modules

 Intelligent  
Simple O&M

- Smart I-V Curve Diagnosis Function: locate PV string faults accurately and automatically detect faults
- Intelligent Fault Detection: AC side voltage and current waveforms real-time recorded, fast fault location
- Support RS485 (WiFi/GPRS/Ethernet optional): remote monitoring and operation via PC or mobile phones

 Reliable  
Worry Free

- IP66 Protection degree: support outdoor installation
- DC & AC Type II SPD: prevent lightning damage
- AFCI Function (Optional): when an arc-fault is detected the inverter immediately stops operation

	XG17KTR	XG20KTR	XG22KTR	XG25KTR
<b>Input (DC)</b>				
Max. Input Power	27.2kW	32kW	35.2kW	40kW
Max. Input Voltage		1100V		
Start Voltage		250V		
Rated Input Voltage		600V		
Full-load MPP Voltage Range	480V ~ 800V		520V ~ 800V	560V ~ 800V
MPPT Voltage Range		200V ~ 1000V		
Number of MPP Trackers		2		
Number of string per MPPT	2 / 2			2 / 3
Max. Current per MPPT	32A			32A / 48A
Max. Short Circuit Current per MPPT		40A		40A / 60A
<b>Output (AC)</b>				
Max. Output Current	27.2A	32.1A	35.3A	39.8A
Rated Output Power	17kW	20kW	22kW	25kW
Max. Output Power	18.8kVA	22.2kVA	24.4kVA	27.5kVA
Rated Grid Frequency		50Hz / 60Hz		
Rated Grid Voltage		230Vac / 400Vac, 3L / N / PE		
Power Factor		>0.99 ( 0.8 leading ~ 0.8 lagging )		
THDi		<3% ( Rated Power )		
<b>Efficiency</b>				
Max. Efficiency		98.40%		
European Efficiency		98.00%		
MPPT Efficiency		99.90%		
<b>Protection</b>				
DC Reverse Polarity Protection		Yes		
Anti-islanding Protection		Yes		
AC Short Circuit Protection		Yes		
Residual Current Monitoring Unit		Yes		
Insulation Resistance Monitoring		Yes		
Ground Fault Monitoring		Yes		
Grid Monitoring		Yes		
PV String Monitoring		Yes		
Surge Protection		Type II		
AFCI Protection		Optional		
<b>Communication</b>				
Display		LCD / LED+APP		
Communication		Standard: RS485 Optional: WiFi / GPRS / Ethernet		
<b>Standard Compliance</b>				
Certification		IEC/EN 62109-1/2, IEC/EN 61000-6-1/3, IEC60068, IEC61683, EN 50549, IEC61727/IEC62116, CEI 0-21, C10/C11, VDE 4105, VDE 0124, RD244, UNE217001, UNE217002, NC RfG, AS4777, NB/T 32004, BIS		
<b>General Data</b>				
Dimensions (W x H x D)		534 x 440 x 220 mm		
Weight		24 kg		
Operating Temperature Range		-30° C ~ +60° C		
Cooling Method		Smart Cooling		
Protection Degree		IP66		
Max. Operating Altitude		4000 m		
Relative Humidity		0 ~ 100%		
Topology		Transformerless		
Night Power Consumption		< 1 W		



INVT Solar Technology (Shenzhen) Co., Ltd.

Sales E-mail: solar@invtsolar.com Service E-mail: solar-service@invtsolar.com Website: www.invtsolar.com



2nd Floor, Block B, INVT Guangming Technology Building, Songbai Road, Matian, Guangming District, Shenzhen, China